


SimSpot spot filter & spot filter (PSR) with pressure shock resistance of 0.7 bar

Questionnaire for quotation

Customer:

Plant type/process:



Product:	Capacity:	t/h	Density:
----------	-----------	-----	----------

Air cap.:	m ³ /h	Max. emission:	20 mg/Nm ³	Hours of operation:
-----------	-------------------	----------------	-----------------------	---------------------

Equipment data:

Type of device: Conveyor Bucket elevator

Conveyor data: Speed: m/s Width: mm Drop height: mm

Bucket elevator data: Speed: m/s Length: mm Width of legs: mm

Pressure shock resistance 0.7 bar Yes No Leg size width x depth: mm

To be completed in case of special temperature, humidity, aggressive environment, etc.:

Product: Sticky Hygroscopic Explosive Abrasive

Allocation of particles: %> my %> my %> my %> my

Air capacity: At temp.: m³/h Nm³/h Max.: m³/h

Filter install.: Indoors Out-of-doors

Temp. inside filter: Normal: °C Max.: °C Min.: °C

Ambient temperature: Normal: °C Max.: °C Min.: °C

Water content: g/kg Dew-point temp.: °C

Aggressive gases: Type: |

EXECUTION OF FILTER

Service door install.: Top Side

Filter mounting: Horizontal Vertical

Product-side parts: Mild steel/primed AISI 304 AISI 304, sanitary

Top sect., inside: Mild steel/primed AISI 304

Filter bags, quality: _____

Comments: _____

Questionnaire completed by: _____ Date: _____